

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 1 of 23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product code : **1130062**

Trade name : **LA LMM-6000SPRAY**
GSLA_LMM-6000 Black Aerosol Spray Can

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Decorative coating

1.3 Details of the supplier of the safety data sheet

Company : Vibrantz GmbH
Gutleutstraße 215
60327 Frankfurt am Main

Telephone : +4969271160

Telefax : +496927116333

E-mail address Responsible/issuing person : sdb@vibrantz.com

1.4 Emergency telephone number

In-Country Number : +(44)-870-8200418

CHEMTREC Global Number : +(1)-703-527-3887 (Call Collect)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 2 of 23

Signal word	:	Danger	
Hazard statements	:	H222 H229 H319 H335 H351	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer.
Precautionary statements	:	Prevention: P201 P210 P211 P251 P280 Storage: P410 + P412	Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Molybdenum(VI) oxide
ammonium metavanadate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : inorganic metal-nonmetal compound
organic solvent
extremely flammable liquefied gas

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 3 of 23

silicatic material
hydrocarbon, aliphatic
inorganic salt

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43- xxxx	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 30 - < 50
Molybdenum(VI) oxide	1313-27-5 215-204-7 042-001-00-9 01-2119488038-30- xxxx	Eye Irrit. 2; H319 Carc. 2; H351 STOT SE 3; H335 (Respiratory system)	>= 20 - < 30
ammonium metavanadate	7803-55-6 232-261-3	Acute Tox. 3; H301 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) Acute toxicity estimate Acute oral toxicity: 275,87 mg/kg	>= 0,1 - < 10
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46- xxxx	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 0,1 - < 10
methanol	67-56-1 200-659-6 603-001-00-X 01-2119392409-28- xxxx	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 % STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 %	>= 1 - < 3

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 4 of 23

		Acute toxicity estimate	
		Acute dermal toxicity: 300 mg/kg	
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36-xxxx	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 0,1 - < 10
		Acute toxicity estimate	
		Acute oral toxicity: 1.200 mg/kg 1.200 mg/kg	
4-methylpentan-2-one	108-10-1 203-550-1 606-004-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 Carc. 2; H351 STOT SE 3; H336 (Central nervous system) EUH066	>= 0,1 - < 1
		Acute toxicity estimate	
		Acute inhalation toxicity (vapour): 11 mg/l	
Substances with a workplace exposure limit :			
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32-xxxx	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	>= 10 - < 20
mica	12001-26-2 310-127-6		>= 0,1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 5 of 23

- If inhaled : If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Rinse mouth immediately with plenty of water and seek medical advice.
Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 6 of 23

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use a water spray to cool fully closed containers. For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Clean contaminated floors and objects thoroughly while observing environmental regulations.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid release to the environment.
Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on a naked flame or any incandescent material.

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 7 of 23

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethanol	64-17-5	TWA	1.000 ppm 1.920 mg/m ³	GB EH40
Molybdenum(VI) oxide	1313-27-5	TWA	5 mg/m ³ (Molybdenum)	GB EH40
		STEL	10 mg/m ³ (Molybdenum)	GB EH40
butane	106-97-8	TWA	600 ppm 1.450 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		STEL	750 ppm 1.810 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
mica	12001-26-2	TWA (Inhalable)	10 mg/m ³	GB EH40
		TWA (Respirable fraction)	0,8 mg/m ³	GB EH40
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	2017/164/EU
	Further information: Indicative			
		STEL	400 ppm 1.468 mg/m ³	2017/164/EU
	Further information: Indicative			
		STEL	400 ppm 1.468 mg/m ³	GB EH40

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY

Product specification **RS_FP_603544**
Version **3.0**
Material number **1130062**

GSLA_LMM-6000 Black Aerosol Spray Can

Revision Date **14.03.2023**
Print Date **15.01.2025**
Page **Page 8 of 23**

		TWA	200 ppm 734 mg/m ³	GB EH40
methanol	67-56-1	TWA	200 ppm 260 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	200 ppm 266 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	250 ppm 333 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 123 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 246 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
ethanol	64-17-5	TWA	1.000 ppm 1.920 mg/m ³	GB EH40
Molybdenum(VI) oxide	1313-27-5	TWA	5 mg/m ³ (Molybdenum)	GB EH40
		STEL	10 mg/m ³ (Molybdenum)	GB EH40
butane	106-97-8	TWA	600 ppm 1.450 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		STEL	750 ppm 1.810 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
mica	12001-26-2	TWA (Inhalable)	10 mg/m ³	GB EH40
		TWA (Respirable fraction)	0,8 mg/m ³	GB EH40
ethyl acetate	141-78-6	TWA	200 ppm	2017/164/EU

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 9 of 23

			734 mg/m3	
	Further information: Indicative			
		STEL	400 ppm 1.468 mg/m3	2017/164/EU
	Further information: Indicative			
		STEL	400 ppm 1.468 mg/m3	GB EH40
		TWA	200 ppm 734 mg/m3	GB EH40
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	200 ppm 266 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	250 ppm 333 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 123 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 246 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
4-methylpentan-2-one	108-10-1	TWA	20 ppm 83 mg/m3	2000/39/EC
	Further information: Indicative			
		STEL	50 ppm 208 mg/m3	2000/39/EC
	Further information: Indicative			
		STEL	100 ppm 416 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY

Product specification **RS_FP_603544**
Version **3.0**
Material number **1130062**

GSLA_LMM-6000 Black Aerosol Spray Can

Revision Date **14.03.2023**
Print Date **15.01.2025**
Page Page 10 of 23

	TWA	50 ppm 208 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT
4-methylpentan-2-one	108-10-1	4-methylpentan-2-one: 20 micromol per litre (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m ³
	Workers	Dermal	Long-term systemic effects	343 mg/kg bw/day
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m ³
	Workers	Inhalation	Acute systemic effects	1091 mg/m ³
	Workers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	89 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethanol	Fresh water	0,96 mg/l
	Marine water	0,79 mg/l
	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Marine sediment	2,9 mg/kg dry weight (d.w.)
	Soil	0,63 mg/kg dry weight (d.w.)
	Sewage treatment plant	580 mg/l
	2-butoxyethanol	Fresh water
Marine water		0,88 mg/l
Sewage treatment plant		463 mg/l
Fresh water sediment		34,6 mg/kg dry weight (d.w.)
Marine sediment		3,46 mg/kg dry weight (d.w.)
	Soil	2,33 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 11 of 23

8.2 Exposure controls

Engineering measures

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection	:	Ensure that eyewash stations and safety showers are close to the workstation location. Tightly fitting safety goggles
Hand protection	:	Wear protective gloves, for example: polyvinyl alcohol or nitrile-butyl-rubber gloves, or similar; Glove thickness: > 0.4 mm and Break Through time: > 480 minutes. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Before removing gloves clean them with soap and water.
Skin and body protection	:	Impervious clothing
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 143
Filter type	:	Particulates type (P)
Protective measures	:	Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	aerosol
Colour	:	black
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	No data available
Flammability	:	No data available
Upper explosion limit / Upper flammability limit	:	19 %(V)
Lower explosion limit / Lower flammability limit	:	1,1 %(V)
Flash point	:	14 °C
Auto-ignition temperature	:	not determined
Decomposition temperature	:	No data available
pH	:	No data available

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 12 of 23

Viscosity
Viscosity, kinematic : No data available

Solubility(ies)
Water solubility : soluble
Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available
Vapour pressure : No data available

Relative density : No data available

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : No data available

Oxidizing properties : No data available

Flammable solids
Burning rate : No data available

Self-ignition : No data available

Evaporation rate : No data available

Refractive index : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 13 of 23

Materials to avoid : Not applicable

10.6 Hazardous decomposition products

Stable under normal conditions.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

ethanol:

Acute dermal toxicity : LD50 (Rabbit): 15.800 mg/kg

ammonium metavanadate:

Acute oral toxicity : LD50 (Rat, male and female): 275,87 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Remarks: Toxic if swallowed.

Acute toxicity estimate: 275,87 mg/kg
Method: Calculation method

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 6.100 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

methanol:

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg
Method: Converted acute toxicity point estimate

2-butoxyethanol:

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 14 of 23

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

LD50 Oral (Rat, male and female): 1.746 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

4-methylpentan-2-one:

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Test atmosphere: vapour
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

butane:

Acute inhalation toxicity : LC50 (Rat, male and female): 658 g/m³
Exposure time: 4 h
Test atmosphere: gas
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

ethanol:

Species : Rabbit
Exposure time : 24 h
Method : OECD Test Guideline 404
Result : No skin irritation

Molybdenum(VI) oxide:

Species : Rabbit
Exposure time : 4 h
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

2-butoxyethanol:

Species : Rabbit

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 15 of 23

Exposure time : 72 h
Method : OECD Test Guideline 404
Result : Irritating to skin.
GLP : yes

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

ethanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Eye irritation

Molybdenum(VI) oxide:

Species : Rabbit
Assessment : Irritating to eyes.
Result : Irritating to eyes.

ammonium metavanadate:

Species : Rabbit
Exposure time : 1 h
Method : OECD Test Guideline 405
Result : Irritating to eyes.
GLP : yes

ethyl acetate:

Species : Rabbit
Result : No eye irritation

2-butoxyethanol:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 16 of 23

STOT - single exposure

May cause respiratory irritation.

Components:

ammonium metavanadate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

ethanol:

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): 9.268 mg/l
Exposure time: 48 h

Molybdenum(VI) oxide:

Toxicity to fish : (Pimephales promelas (fathead minnow)): 370 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility

ammonium metavanadate:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 17 of 23

Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 560 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 3.300 mg/l
Exposure time: 48 h

methanol:

Toxicity to fish : LC50 (Fish): 28.200 mg/l
Exposure time: 96 h

2-butoxyethanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.490 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.800 mg/l
Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

ethanol:

Partition coefficient: n-octanol/water : log Pow: -0,349 (24 °C)

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0,73 (20 °C)

methanol:

Partition coefficient: n-octanol/water : log Pow: -0,77

2-butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0,77 (20 °C)
pH: 7

4-methylpentan-2-one:

Partition coefficient: n-octanol/water : Pow: 1,19

butane:

Partition coefficient: n-octanol/water : log Pow: 2,745

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 18 of 23

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : None known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Send to a licensed waste management company.
Dispose of wastes in an approved waste disposal facility.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
-

SECTION 14: Transport information

14.1 UN number

- ADR : UN 1950
IMDG : UN 1950
IATA : UN 1950

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 19 of 23

14.2 UN proper shipping name

ADR : AEROSOLS, FLAMMABLE, AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : 2.1

IATA (Passenger)
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : 2.1

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 20 of 23

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: methanol (Number on list 69)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Neither banned nor restricted

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Neither banned nor restricted

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Neither banned nor restricted

UK REACH List of substances subject to authorisation (Annex XIV) : Neither banned nor restricted

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

18 Liquefied extremely flammable gases (including LPG) and natural gas

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

Other regulations:

The components of this product are reported in the following inventories:

TCSI (Taiwan) : On the inventory, or in compliance with the inventory

TSCA (United States) : All substances listed as active on the TSCA inventory

AIC (Australia) : All components are listed on the inventory, regulatory obligations/restrictions apply

DSL/NDSL (Canada) : All components of this product are on the Canadian DSL

ENCS (Japan) : Not in compliance with the inventory

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 21 of 23

ISHL (Japan)	:	Not in compliance with the inventory
PICCS (Philippines)	:	On the inventory, or in compliance with the inventory
IECSC (China)	:	On the inventory, or in compliance with the inventory
SWISS (Switzerland)	:	On the inventory, or in compliance with the inventory
EINECS (European Union)	:	On the inventory, or in compliance with the inventory
CICR (Turkey)	:	Not in compliance with the inventory
TECI (Thailand)	:	On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H220	:	Extremely flammable gas.
H225	:	Highly flammable liquid and vapour.
H280	:	Contains gas under pressure; may explode if heated.
H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H311	:	Toxic in contact with skin.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H351	:	Suspected of causing cancer.
H370	:	Causes damage to organs.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 22 of 23

2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
Carc. 2	H351
STOT SE 3	H335

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

SAFETY DATA SHEET

According to (EC) No. 1907/2006, as amended

LA LMM-6000SPRAY		GSLA_LMM-6000 Black Aerosol Spray Can	
Product specification	RS_FP_603544	Revision Date	14.03.2023
Version	3.0	Print Date	15.01.2025
Material number	1130062	Page	Page 23 of 23

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN